

ADHESIVES

Adhesives

A300

HIGH PERFORMANCE ADHESIVE FOR CORK-BASED UNDERLAYS



Quantities available

3.5 kg
6 kg



Bucket dimensions

3.5 kg · ø 19.5 x 13.5 cm
6 kg · ø 22 x 19 cm



SPECIAL PROPERTIES

- Solvent-free*
- Suitable for underfloor heating
- High initial strength
- Suitable for chair castors
- Optimised for floorings with vinyl backing
- Based on the criteria of GEV (Association for Emission-controlled Laying Materials), classified as Emicode EC1PLUS: The premium category, describing the limit of technological feasibility

* Solvent-free according to the definition of TRGS 610.

TECHNICAL INFORMATION

Raw material basis	Acrylate dispersion
Cleaning agent	Water before adhesive dries
Application method	With toothed trowel TKB A2 on the subfloor. An absorbent substrate is needed as well the climate conditions for glue down.
Consumption	Approx. 350 g/m ² with TKB A2
Airing time	None
Open time	Approx. 20 minutes
Storage temperature	Do not store below 5° C
Storage time	Approx. 12 months at room temperature
Giscode	D 1
Emicode ACC. to GEV	EC1 Plus



VN13

HIGH PERFORMANCE ADHESIVE FOR CORK WALL COVERINGS



Quantities available

2.5 kg



Bucket dimensions

2.5 kg · ø 19.5 x 13.5 cm

SPECIAL PROPERTIES

- Solvent-free*
- Very low in emissions**
- Adjusted to the colour of natural cork

* Solvent-free according to the definition of the TRGS 610.

** Based on the criteria of GEV (Association for Emission-controlled Laying Materials), classified as Emicode EC1: very low in emissions.

TECHNICAL INFORMATION

Raw material basis	Synthetic resin dispersion
Cleaning agent	Water before adhesive dries
Application method	For cork wall covering with TKB B1; For polystyrene hard foam tiles and soft-fibre insulation tiles in spots or strips. An absorbent wall is needed as well the climate conditions for glue down.
Consumption	Approx. 400–500 g/m ² for cork wall coverings, approx. 600–1000 g/m ² for polystyrene and soft-fibre tiles
Airing time	None
Open time	Approx. 5–10 minutes, depending on the applied quantity
Storage temperature	Do not store below 5° C
Storage time	Approx. 12 months at room temperature
Giscode:	D 1
Emicode ACC. to GEV:	EC1



AMORIM CORK SOLUTIONS

AMORIM CORK SOLUTIONS

R. Comendador Américo Ferreira Amorim, 260
4535-186, Mozelos VFR, Portugal
T. +351 22 747 5300
F. +351 22 747 5301
E. mail.acs@amorim.com

AMORIM CORK SOLUTIONS USA

26112 110th Street
Trevor, WI 53179, USA
T. +1 262 862 2311
F. +1 262 862 2500
E. mail.acs.usa@amorim.com

www.amorimcorksolutions.com

The data provided in this brochure refers to typical figures. This information is not intended to be used as a purchasing specification and does not imply suitability for use in any specific application. Failure to select the proper product may result in either product damage or personal injury. Please contact Amorim Cork Solutions regarding recommendations for specific applications. Amorim Cork Solutions expressly disclaims all warranties, including any implied warranties of merchantability or of fitness for any particular purpose. Amorim Cork Solutions shall not be liable for any indirect, special, incidental, consequential or punitive damages as a result of using the information listed in this brochure, any of its material specification sheets, its products or any future use or re-use of them by any person or entity. For contractual purposes, please request our Product Specifications Sheet (PDA).

